

EBOX-333x Series, VGA, LAN x 1, RS-485

Model Type	EB-3330-851	EB-3330-852	EB-3330-851C1	EB-3330-851C2	EB-3330-851C3	EB-3330-852C1	EB-3330-852C2	EB-3330-851221	EB-3330-851221C1	EB-3330-851221C2
	EB-3332-851	EB-3332-852	EB-3332-851C1	EB-3332-851C2	EB-3332-851C3	EB-3332-852C1	EB-3332-852C2	EB-3332-851221	EB-332-851221C1	EB-3332-851221C2
Processor	Vortex86DX2 (933MHz)									
BIOS	AMI BIOS									
Memory	Onboard 1GB DDR2 for 3330 Series/ Onboard 2GB DDR2 for 3332 Series									
VGA	Integrated Graphics Chip/ D-Sub 15-pin									
Ethernet	10/100 Mbps LAN x 1 (RJ-45 connector, Built-in PXE diskless boot)									
USB (2.0)	External: 3 ports (Front x 2, Rear x 1) Internal: 1 port									
HD Audio	Line out									
SD Slot	1x									
SATA	1x									
I/O	COM1	RS-485	RS-485	RS-485	RS-485	RS-485	RS-485	RS-485	RS-485	RS-485
	COM2	N/A	RS-485	RS-232	RS-232	RS-232	RS-485	RS-485	RS-422	RS-422
	COM3	N/A	N/A	RS-232	RS-232	RS-232	RS-232	N/A	RS-232	RS-232
	COM4	N/A	N/A	N/A	RS-232	N/A	RS-232		N/A	RS-232
Auto Power On	Yes									
Power	DC +8V ~ +15V									
Dimensions	115 x 115 x 35 mm									
Unit Net Weight	510g									
Operation Temp.	5 ~ 50 °C									
Certifications	CE, FCC, VCCI									
Optional	1. Mic input 2. Internal SD Card slot 3. TTL Level RS-232									
Note	RS-232 COM ports in Full 9pin									

Features:

- High performance
- Fanless design
- VESA mounting support
- Vortex86DX2 (933MHz)
- Onboard 1GB/ 2GB DDR2
- PXE Diskless Boot
- 2.5" SATA HDD support
- SATA DOM support
- SD, SDHC support
- WiFi Dongle support (Optional)
- USB V2.0 port x 3
- RS-232 Up to 3 ports (Optional)
- RS-485 Up to 2 ports (Optional)
- RS-422 port x 1 (Optional)
- Auto Power On support
- Ultra low power

