

EBOX-333x Series, HDMI, LAN x 1, RS-485

Model Type	EB-3330-851DMI	EB-3330-852DMI	EB-3330-851C1DMI	EB-3330-851C2DMI	EB-3330-851C3DMI	EB-3330-852C1DMI	EB-3330-852C2DMI	3330-851221DMI	3330-851221C1DMI	3330-851221C2DMI	
	EB-3332-851DMI	EB-3332-852DM	EB-3332-851C1DMI	EB-3332-851C2DMI	EB-3332-851C3DMI	EB-3332-852C1DMI	EB-3332-852C2DMI	3332-851221DMI	3332-851221C1DMI	3332-851221C2DMI	
Processor	Vortex86DX2 (933MHz)										
BIOS	AMI BIOS										
Memory	Onboard 1GB DDR2 for 3330 Serie/ Onboard 2GB DDR2 for 3332 Series										
VGA	HDMI										
Ethernet	10/100 Mbps LAN x 1 (RJ-45 connector, Built-in PXE diskless boot)										
USB (2.0)	External: 3 ports (Front x 2, Rear x 1) Internal: 1 port										
HD Audio	Mic in										
PS2	PS/2 for Keyboard/ Mouse x 1										
SD Slot	1x										
SATA	1x										
I/O	COM1	RS-485	RS-485	RS-485	RS-485	RS-485	RS-485	RS-485	RS-485	RS-485	
	COM2	N/A	RS-485	RS-232	RS-232	RS-232	RS-485	RS-485	RS-422	RS-422	
	COM3		N/A	N/A	RS-232	RS-232	RS-232	RS-232	N/A	RS-232	RS-232
	COM4		N/A	N/A	N/A	RS-232	N/A	RS-232		N/A	RS-232
Auto Power On	Yes										
Power	DC +8V ~ +15V										
Dimensions	115 x 115 x 35 mm										
Unit Net Weight	500g										
Operation Temp.	5 ~ 50 °C										
Certifications	CE, FCC, VCCI										
Optional	1. Line out 2. Internal SD Card slot 3. TTL Level RS-232										
Note	RS-232 COM ports in Full 9pin										

Features:

- High performance
- Fanless design
- VESA mounting support
- Vortex86DX2 (933MHz)
- Onboard 1GB/ 2GB DDR2
- HDMI video output
- PXE Diskless Boot
- 2.5" SATA HDD support
- SATA DOM support
- SD, SDHC support
- WiFi Dongle support (Optional)
- USB V2.0 port x 3
- RS-232 Up to 3 ports (Optional)
- RS-485 Up to 2 ports (Optional)
- RS-422 port x 1 (Optional)
- Auto Power On support
- Ultra low power

