

EBOX-333x Series, VGA, LAN x 2, RS-232

Model Type	EB-3330-L2SS	EB-3330-L2C1	EB-3330-L2C2	EB-3330-L2C3	EB-3330-L2C4
	EB-3332-L2SS	EB-3332-L2C1	EB-3332-L2C2	EB-3332-L2C3	EB-3332-L2C4
Processor	Vortex86DX2 (933MHz)				
BIOS	AMI BIOS				
Memory	Onboard 1GB DDR2 for 3330 Series/ Onboard 2GB DDR2 for 3332 Series				
VGA	Integrated Graphics Chip/ D-Sub 15-pin				
Ethernet	10/100 Mbps LAN x 1, 1G LAN x 1 (RJ-45 connector, Built-in PXE diskless boot)				
USB (2.0)	External: 3 ports (Front x 2, Rear x 1) Internal: 1 port				
HD Audio	Line out				
SD Slot	1x				
SATA	1x				
I/O	COM1	RS-232	RS-232	RS-232	RS-232
	COM2	N/A	RS-232	RS-232	RS-232
	COM3		N/A	RS-232	RS-232
	COM4		N/A	N/A	RS-232
Auto Power On	Yes				
Power	DC +8V ~ +15V				
Dimensions	115 x 115 x 35 mm				
Unit Net Weight	510g				
Operation Temp.	5 ~ 50 °C				
Certifications	CE, FCC, VCCI				
Optional	1. Mic input 2. Internal SD Card slot 3. TTL Level RS-232				
Note	RS-232 COM ports in Full 9pin				

Features:

- High performance
- Fanless design
- VESA mounting support
- Vortex86DX2 (933MHz)
- Onboard 1GB/ 2GB DDR2
- PXE Diskless Boot
- 2.5" SATA HDD support
- SATA DOM support
- SD, SDHC support
- WiFi Dongle support (Optional)
- USB V2.0 port x 3
- 10/100 Mbps LAN x 1, 1Gbps LAN x 1
- RS-232 Up to 4 ports (Optional)
- Auto Power On support
- Ultra low power

