

SoM-5282M

User Manual

REV. 1.0

Copyright 2005,
EMAC, Inc.

EMAC, inc.
EQUIPMENT MONITOR AND CONTROL
2390 EMAC Way, Carbondale, Illinois 62901
World Wide Web: <http://www.emacinc.com>
Phone: (618) 529-4525 Fax: (618) 457-0110

Table of Contents

1. Disclaimer	1
2. Introduction	2
2.1. Features.....	2
3. Hardware	3
3.1. Specifications.....	3
3.2. Real Time Clock.....	3
3.3. External Connections	4
3.3.1. External Bus.....	4
3.3.2. BDM – Module specific interface	5
3.3.3. JTAG/GPTB	5
3.3.4. One-Wire	6
3.3.5. Ethernet	6
3.3.6. QSPI.....	7
3.3.7. Serial Ports.....	8
3.3.8. GPIO	9
3.3.9. CAN.....	9
3.4. Power.....	10
3.5. Boot Options	11
4. Design Considerations.....	11
4.1. The EMAC SoM Carrier-SoM-100ES.....	11
4.2. Configuration.....	11
4.3. Power.....	12
4.3.1. Legacy	12
4.3.2. Battery Backup	12
4.3.3. Analog Voltage	13
5. Software.....	13
5.1. Eclipse	13
5.1.1. Eclipse CDT plug-in	14
5.2. Das U-Boot.....	14
5.3. µClinux.....	14
5.3.1. µClinux with RTAI.....	14
5.3.2. µClinux 2.6 drivers	14
5.4. M68k-Elf-Tools.....	15
5.5. Commercial Solutions.....	16
5.6. Java.....	16

1. Disclaimer

EMAC Inc. does not assume any liability arising out of the application or use of any of its products or designs. Products designed or distributed by EMAC Inc. are not intended for, or authorized to be used in, applications such as life support systems or for any other use in which the failure of the product could potentially result in personal injury, death or property damage.

If EMAC Inc. products are used in any of the aforementioned unintended or unauthorized applications, Purchaser shall indemnify and hold EMAC Inc. and its employees and officers harmless against all claims, costs, damages, expenses, and attorney fees that may directly or indirectly arise out of any claim of personal injury, death or property damage associated with such unintended or unauthorized use, even if it is alleged that EMAC Inc. was negligent in the design or manufacture of the product.

EMAC Inc. reserves the right to make changes to any products with the intent to improve overall quality, without further notification.

2. Introduction



This document describes EMAC's SoM-5282M (SBC) module. The SoM-5282M is a system on module, designed to be backwards compatible with EMAC's SoM-400EM, but taking advantage of the more powerful MCF5282 processor.

Like the SoM-400EM, the SoM-5282M has an onboard PHY, 3 serial ports, a RTC, a programmable clock synthesizer, onboard flash and RAM.

In addition to these standard SoM features, the SoM-5282M also features a much faster 32-bit core, open source software support, and a wide range of controller IO pins.

2.1. Features

- **Small, SoM compatible SODIMM form factor 2.66" x 1.50"**
- **10/100 Base-T Ethernet with on-board PHY**
- **RTC**
- **8/16M DRAM**
- **2/4M Flash**
- **PLL synthesized clocks, 14.3MHz, 8MHz, 200KHz**
- **Strong open source support including Das U-Boot and μ Clinux**
- **Standard core M5282EVB architecture compatible with most commercial software packages**
- **Freescale MCF5282 Coldfire core with:**
 - **64MHz 32-bit RISC core**
 - **2K instruction and data cache**
 - **DRAM controller**
 - **BDM**
 - **Queued SPI Port**
 - **3 Serial Ports with handshake lines**
 - **8 channels of 10-bit A/D**
 - **General Purpose Timers with external interface for Counters/PWM**
 - **JTAG**
 - **2.0 CAN**

3. Hardware

3.1. Specifications

- **VOLTAGE REQUIREMENTS:** 3.3V (and 5V for 5V analog if required)
- **CURRENT REQUIREMENTS:** 500 mA max.
- **OPERATING TEMPERATURE:** 0 - 70 degrees Centigrade, humidity range without condensation 0% to 90% RH.
- **DIMENSIONS:** SODIMM form factor with dimensions of 2.66" x 1.50".
- **PROCESSOR:** Freescale MCF5282 microcontroller
- **DRAM:** 8 or 6M of fast DRAM
- **FLASH:** 2 or 4M flash
- **RTC**
- **I/O:** 144 pin SODIMM connection providing
 - **External Bus Interface:** 22 address x 16 data
 - **BDM:** standard background debug module
 - **Ethernet:** onboard PHY provides 10/100 base-T Ethernet signals.
 - **QSPI:** queued SPI port with 3 multiplex-able chip selects
 - **Serial Ports:** 3 serial ports or 14 pins of GPIO
 - **A/D:** 8 multiplex-able AtoD inputs or 8 GPIO
 - **External IRQs:** 6 external IRQs or 6 GPIO
 - **Timer/Counters:** 4 input capture/output compare timer pins with sync pin or 5 GPIO
 - **JTAG:** bit banded JTAG out, or 4 additional general-purpose timer pins.
 - **CAN:** 2.0 CAN interface or 2 GPIO
 - **CLOCKS:** PLL synthesized 8M, 200K, 14.3M clock outputs

3.2. Real Time Clock

The SoM-5282M provides a DS1305 real time clock/calendar on board the module. Battery backup is provided by the carrier board through the VSTBY pin.

3.3. External Connections

The SoM-5282 connects to a carrier board containing its connectors, power supply and any expansion IO, through a standard gold-plated SODIMM 144 pin connection (top half shown below).



The SoM model will fit in any standard SODIMM socket. These connections are designed to be compatible with all EMAC SoM products.

The remainder of this section describes the pinout as it applies specifically to the SoM-5282M processor.

3.3.1. External Bus

The SoM-5282M provides a flexible external bus for connecting peripherals. The CPLD of the SoM-100ES connects through a subset of these connections.

SODIMM Pin#	Pin Name	Processor Pin	Description
100	GP_CS1	~CS1~/PJ1	General purpose Chip select 1 from the processor or GPIO
98	GP_CS2	~CS2~/PJ2	General purpose Chip select 2 from the processor or GPIO
108	GP_CS3	~CS3~/PJ3	General purpose Chip select 3 from the processor or GPIO
16	~OE	~OE~/PE7	Output enable, asserts when an external device can drive the data bus or GPIO
83	~WR	R/~W~/PE4	Indicates the direction of the bus transfer or GPIO
6	~RST_IN	~RSTIN	Reset input to the processor.
43	~RST_OUT	~RSTOUT	Reset output from the processor
44	~EA	~TEA~/PE5	Error condition on a bus transfer or GPIO
85	~RD/TIP	NC	Not connected on the SoM-5282M
72	ALE/~TS	~TS~/PE1/SYN CA	Transfer-Start Asserted at the start of a transfer to indicate a valid address or GPIO
26,35,33,31,28,109,111,113,10,12,18,14,37,5,11,9,7,13,97,17,15,104	Address bus A0-A21	Address bus A0-A21	Address lines from the processor. These same lines are tied to the internal memory of the SoM-100ES, so must always be used as address lines (not GPIO)
29,27,25,22,23,21,19,20,8,24,34,70,77,81,84,86	Data Bus D0-D15	Data Bus D16-D31	High data lines from the processor, these are used for word access to peripherals as per the design recommendations. Again, like the data lines, these pins must be used as data pins only as they are attached to the memory of the module.

3.3.2. BDM – Module specific interface

The SoM-5282M brings out the full BDM connection of the processor. These pins are routed on the SoM-100ES to a P&E wiggler compatible header, which can be used for full, low level source debugging through either a proprietary package such as Metroworks Codewarrior, or an open source program such as gdb, which fully supports source level debugging of the processor. This can even be used to step through the low level internals of the Linux kernel itself.

On the SoM-5282M, these pins come out the pins that have been delegated “module specific” in the SoM specification.

SODIMM Pin#	Pin Name	Processor Pin	Description
45	MS0	~BKPT~/TMS	Hardware breakpoint assertion
46	MS1	~TA~/PE6	External data transfer complete or GPIO
47	MS2	DSCLK/~TRST	Serial interface to debug module
48	MS3	DSI/TDI	Bit communication for module commands
49	MS4	DSO/TDO	Bit communication for command responses
50	MS5	NC	Reset input to the processor.
51	MS6	NC	Reset output from the processor
57,56,55,54	MS10-7	DDATA0-3	Display captured process data
60	MS11	TCLK	JTAG test logic clock
61	MS12	CLOCKOUT	Reflects the system clock
64,65,66,67	MS13-16	PST0-3	Indicates core status

3.3.3. JTAG/GPTB

The SoM specifications for the JTAG header are filled by GPIO/TimerB pins on the SoM-5282. These connections will allow CPLD/FPGAs to be programmed in circuit via a program running from the processor.

Alternatively these pins can be used as GPT pins, which can be used as counters or PWM.

SODIMM Pin#	Pin Name	Processor Pin	Description
139	JTAG_TCK	GPTB0/PTB0	JTAG clock -> port B0
137	JTAG_TDI	GPTB1/PTB1	JTAG serial in -> port B1
138	JTAG_TDO	GPTB2/PTB2	JTAG serial out ->port B2
140	JTAG_TMS	GPTB3/PTB3	JTAG operation mode ->port B3

3.3.4. One-Wire

The SoM specification calls for a one-wire port. On the SoM-5282M this is just connected to GPIO pin of the processor for bit-banged operation since the 5282 does not natively support one-wire.

SODIMM Pin#	Pin Name	Processor Pin	Description
116	LOCAL1W	SIZ0/PE2/ SYNCB	Maxim One-Wire network signal/GPIO. Connected directly to PE2 of the processor. This configuration will not be capable of driving standard One-Wire networks, or OW devices expecting power from the pin. Users with demanding one-wire applications are referred to the SoM-400EM or the SoM-NE64EM.

3.3.5. Ethernet

The SoM-5282M provides a LX972 Ethernet PHY IC on board. Carrier designers need only run these lines through the appropriate magnetics layer to have a functional Ethernet connection.

The LED/configuration pins state at reset determines the Ethernet's configuration (10-baseT, 100-base-T, autoconfig) and the function of the LED's. The SoM-100ES-R3 pulls them all high, which configures the chip for network autoconfig, with LED1 functioning as active low link, and LED3 functioning as active low Rx status.

SODIMM Pin#	Pin Name	LXT972 Pin	Description
45	LED_TX/ CFG_0	LED_TX/ CFG_0	Ethernet LED/Configuration pin
46	LED_LINK/ CFG_1	LED_LINK/ CFG_1	Ethernet LED/Configuration pin
47	LED_RX/ CFG_2	LED_RX/ CFG_2	Ethernet LED/Configuration pin
48	Ethernet_Rx-	Ethernet_Rx-	Low differential Ethernet receive line
49	Ethernet_Rx+	Ethernet_Rx+	High differential Ethernet receive line
50	Ethernet_Tx-	Ethernet_Tx-	Low differential Ethernet transmit line
51	Ethernet_Tx+	Ethernet_Tx+	High differential Ethernet transmit line

3.3.6. QSPI

The Coldfire processor provides a queued SPI module for communicating with peripheral devices. This bus is connected internally to the RTC, which uses SPI_CS3 (not brought out to the card fingers). Linux users can use the open source mcf_qspi driver provided by EMAC, or the earlier 2.4 driver available in the main μ Clinux tree.

SODIMM Pin#	Pin Name	Processor Pin	Description
122	SPI_MI	QSPI_DIN/PQS1	QSPI serial data in
121	SPI_MO	QSPI_DOUT/PQS0	QSPI serial data out
120	SPI__SCK	QSPI_CLK/PQS2	QSPI serial clock out
123	SPI_CS0	QSPI_CS0/PQS3	QSPI slave select line 3
124	SPI_CS1	QSPI_CS1/PQS4	QSPI slave select line 4
110	SPI_CS2*	QSPI_CS2/PQS5	QSPI slave select line 5

3.3.7. Serial Ports

The SoM-5282 provides 3 serial ports. Typically the SoM specification calls for Com0 to be the terminal port, which is the default for both Maxims Tini OS, and μ Clinux. However, Com0 on the 5282 processor provides handshaking pins, which go to waste on a terminal port. Therefore the SoM-5282M design swaps Com1 and Com3. A patch is provided for Linux 2.4 and Linux 2.6 to swap them back in the OS.

SODIMM Pin#	Pin Name	Processor Pin	Description
71	COM1_RXD	SDA/PAS1/ URXD2	COM1 receive/GPIO
73	COM1_TXD	SCL/PAS0/ UTXD2	COM1 transmit/GPIO
38	COM2_RXD	URXD1/PUA3	COM2 receive/GPIO
36	COM2_TXD	UTXD1/PUA2	COM2 transmit/GPIO
82	COM2_RTS/GPIO	DTOUT1/PTD2/~URTS1-0	COM2 RTS/GPIO
78	COM2_CTS/GPIO	DTOUT0/PTD0/~UCTS1-0	COM2 CTS/GPIO
103	COM3_RXD_	URXD0/PUA1	COM3 receive/GPIO
102	COM3_TXD	UTXD0/PUA0	COM3 receive/GPIO
107	COM3_DSR/GPIO	DTIN0/PTD1/ ~UCTS1-0	COM3 DSR /GPIO
106	COM3_DTR/GPIO	DTIN1/PTD3/ ~URTS1-0	COM3 DTR/GPIO
76	COM3_RI/GPIO	DTIN2/PTC1/ ~UCTS1-0	COM3 RING/GPIO
30	COM3_DCD/GPIO	DTIN3/PTC3/ ~URTS1-0	COM3 DCD/GPIO
39	COM3_RTS/GPIO	DTOUT3/PTC2/~URTS1-0	COM3 RTS/GPIO
79	COM3_CTS/GPIO	DTOUT2/PTC0/~UCTS1-0	COM3 CTS/GPIO

3.3.8. GPIO

This section provides for the SoM general purpose IO section. With the exception of the clocks, all of these pins can be configured to be general-purpose digital ports. They can also be configured to take advantage of several of the functions of the 5282's internal silicon. All of the internal A/D ports are brought out here, as well as all of the available IRQs and the pins for general-purpose timer A.

A/D:

The Analog to digital pins can handle 8 channels directly, or can multiplex up to 18 inputs. It can handle 10bit resolution and 7us conversion, with the enhanced multiply and accumulate unit behind it, this can make quite a capable signal processor.

Timer/Counters:

General-purpose timer modules on the Coldfire are 16-bit timers; with independently programmable input-capture or output compare lines. These can be used for a wide variety of timed applications, including counters and PWM.

For more information on the AtoD and Timer functions of the MCF5282 processor, users are referred to the *MCF5282 ColdFire Microcontroller User's Manual*.

SODIMM Pin#	Pin Name	Processor Pin	Description
75	IRQ1/GPIO	~IRQ1~/PNQ1	edge port IRQ 1/GPIO
32	IRQ3/GPIO	~IRQ3~/PNQ3	edge port IRQ 3/GPIO
40	GPIO0/IRQ4*	~IRQ4~/PNQ4	edge port IRQ 4/GPIO0
42	GPIO1/IRQ5*	~IRQ5~/PNQ5	edge port IRQ 5/GPIO1
87	GPIO2/IRQ6*	~IRQ6~/PNQ6	edge port IRQ 6/GPIO2
80	GPIO3/IRQ7*	~IRQ7~/PNQ7	edge port IRQ7/GPIO3
125	GPIO4	GPTA0/PTA0	Timer A GPT0 signal or GPIO4
126	GPIO5	GPTA1/PTA1	Timer A GPT1 signal or GPIO5
127	GPIO6	GPTA2/PTA2	Timer A GPT2 signal or GPIO6
128	GPIO7	GPTA3/PTA3	Timer A GPT3 signal or GPIO7
129	GPIO8	AN0/PQB0/ANW	Queued AtoD0/GPIO8
130	GPIO9	AN1/PQB1/ANX	Queued AtoD1/GPIO9
131	GPIO10	AN2/PQB2/ANY	Queued AtoD2/GPIO10
132	GPIO11	AN3/PQB3/ANZ	Queued AtoD3/GPIO11
133	GPIO12	AN52/PQA0/MA0	Queued AtoD4/GPIO12/ Analog multiplexer control low
134	GPIO13	AN53/PQA1/MA1	Queued AtoD5/GPIO13 Analog multiplexer control high
135	GPIO14	AN55/PQA3/ETRIG1	Queued AtoD6/GPIO14/External Analog Queue trigger
136	GPIO15	AN56/PQA4/ETRIG2	Queued AtoD7/GPIO15/External Analog Queue trigger
105	~LDAC/~GPIO	SIZ1/PE3/SYNCA	LDAC control for external DtoA converter or GPIO or timer A external sync
114	8MHz	8MHz	General purpose 8MHz clock
115	200KHz	200KHz	General purpose 200KHz clock
117	14.3MHz	14.3MHz	General purpose 14.3MHz clock

3.3.9. CAN

The 5282 processor provides a full 2.0 queued CAN bus implementation. Note: check the 5282 errata sheets for potential problems when using the CAN bus.

SODIMM Pin#	Pin Name	Processor Pin	Description
96	P5.0/CAN_TX	CANTX/PAS2/U TXD2	CAN transmit
95	P5.1/CAN_RX	CANRX/PAS3/U RXD2	CAN receive

3.4. Power

The SoM-5282M requires a 3.3V rail to supply core voltage to the processor. It also provides several other voltage inputs which can be used to enable and change the characteristics of different parts of the module (NVRAM, 5V analog, filtered analog referenced). If these functions are not required their power pins can just be tied to 3.3V.

SODIMM Pin#	Pin Name	Processor pin- SoM connection	Description
3,4,141,142	3.3VCC	3.3VCC	3.3 Volt voltage core to the processor
1,2,52,53, 58,59,62,63, 68,69,143,1, 44	GND	GND	Ground
119	VSTBY	VSTBY-RTC bat backup	Voltage standby, this is the backup voltage provided to the internal RAM of the processor, as well as to the voltage backup of the RTC. If non-volatile RAM, RTC readings are not important for the application, this can be attached to the 3.3V rail.
118	VPULLUP	NA-RTC power	This is a 5V input to the SoM, provided here for backwards compatibility. If the application in question is 5282 specific, it can be connected to 3.3V(the RTC can accept a 3.3V power supply)
101	VDDA/VDDH	VDDA/VDDH	Analog power. This voltage provides power to the internal analog circuitry of the 5282 processor. It can run anywhere from the 3.3V rail to the 6V. This voltage will determine the maximum value of the reference voltage, and will be the voltage driven out when the pins are used as outputs. Note: During power up VDDA/VDDH should never trail the 3.3V power signal by more than .3 volts. This can lead to an internal latch up of the processor.
99	VRH	VRH	Analog Reference voltage. This is the reference signal the Analog inputs use to represent the maximum voltage for digital conversion. This input cannot be higher than VDDA/VDDH.

3.5. Boot Options

The SoM specification provides two pins for boot time configuration. On the SoM-5282M, these are JTAG_EN and PTA0. JTAG_EN is a hardware configuration pin, that enables JTAG functionality over the BDM pins. PTA0 is the same pin as GPIO pin 4, and is brought out here as well for hardware compatibility. It has no hardware configuration function, and user could use software to code a boot option. This may be changed in a future revision to an RCON function.

SODIMM Pin#	Pin Name	Processor Pin	Description
41	BOOT_OPTION1	JTAG_EN	Enable JTAG over the BDM pins
74	BOOT_OPTION2	GPTA0/PTA0	User Defined/GPIO

4. Design Considerations

One of the goals of the SoM-5282M is to provide a modular, flexible and inexpensive solution capable of delivering high-end microcontroller performance.

4.1. The EMAC SoM Carrier-SoM-100ES

EMAC provides an off the shelf carrier for it's SoM modules, the SoM-100ES, which provides power to SoM modules and provides them with an extended range of I/O. This board comes with full schematics and BOM, and can be used as is, or as a reference for a customer's own design.


<http://www.emacinc.com/som/som100es.htm>

EMAC also offers a semi-custom engineering service. By modifying an existing design, EMAC can offer a quick turn, low cost engineering, for your specific application.



4.2. Configuration

At reset, the SoM-5282R0's processor requires its default configuration to be latched onto its data lines at reset. A diagram from the SoM-100ES schematic is shown below, showing a popular valid configuration used in most 5282 products. For further details about Coldfire processor configuration, see the *MCF5282 ColdFire Microcontroller User's Manual* section 27, the CCM. Also refer to the carrier board schematic.



4.3. Power

The SoM-5282M requires a core voltage of 3.3V and 500mA. For a bare-bones population, users can get away with using only 3.3V, and simply provide this to all the voltage inputs listed in 2.3.10. This, however, will provide only a subset of the 5282's full capability.

4.3.1. Legacy

VPULLUP is a legacy connection, required to support the SoM-400EM and may be used in future SoM modules. If general SoM compatibility is not an issue then this can be tied to 3.3V.

4.3.2. Battery Backup

The SoM-5282M contains 3 potentially non-volatile memory areas, the flash, the real time clock, and the internal RAM of the processor. The flash is always non-volatile, but the internal RAM and real time clock require a backup voltage to maintain their data. This backup voltage comes from the VSTBY pin, it should be between 1.8 and 3.6 volts, and be capable of providing a instantaneous surge of 7 mA.

The battery backed RAM will draw 20 μ A while no power is supplied to the board, and the RTC will draw 400 nA. Since the RAM's current draw is so much higher than the RTC, the SoM-5282 provides a zero-ohm resistor in series with the RAM's VSTBY, which can be removed from the module if it's not needed. If the RTC and the NVRAM are not needed, this can just be tied to 3.3V.

The SoM-100ES provides battery backup voltage through a socketable BR2032, which is a standard 3V 190mA/H 20MM coin battery that can be picked up from most electronics stores.

4.3.3. Analog Voltage

When designing power for the Analog subsystem there are 4 major considerations, range and accuracy output drive, and rise time.

- **Range**
The VDDA/VDDH pins provide the range. These pins provide power to the analog subsystem, and can take any voltage from 3.3 to 6Volts. The power supplied to the analog subsystem limits the range of voltages that can be accurately measured. The internal analog converters cannot measure a voltage higher than their power rail.
- **Accuracy**
The accuracy of the A/D converters is determined by the VRH pin, which provides the reference voltage to the analog subsystem. The stability of the voltage between this pin and ground will effect the accuracy of the subsystem's measurements. For many cases a filter cap is sufficient, since these are only 10 bit converters, however in some environments more robust filters may need to be employed. The VRH pin cannot be at a higher voltage than VDDA/VDDH.
- **Drive**
Another consideration when designing the Analog power supply is the output drive. The A/D conversion pins are also configurable as outputs. In this mode the output voltage will drive to the voltage supplied on VDDA/VDDH. The SoM-100ES provides 5.6 volts to VDDA/VDDH through a diode drop from a charge pump to the 5V rail, and provides the reference voltage through a standard ref-02 IC.
- **Rise Time**
The final consideration for Analog power design is the rise time. MCF5282 processors run the risk of locking up if their core 3.3 voltage gets further than .3 volts ahead of VDDA/VDDH during power up. Therefore if separate supplies are used some sort of sequencing must be considered. The SoM-100ES drains its 3.3V rail through a power diode to the 5.6 volt rail, which forces the analog subsystem to follow the main rail closely enough to avoid any potential lockups.

If users don't need highly accurate readings, and are ok with a 3 volt limitation on the analog readings, then both VRH and VDDA/VDDH can be tied to 3.3V. For a more in-depth description of Analog power design users are referred to section 28 of the *MCF5282 ColdFire Microcontroller User's Manual*.

5. Software

The SoM-5282M offers a wide variety of software support from both open source and proprietary sources. The hardware core was designed to be software compatible with the Motorola M5282EVB reference design, which is supported in most Coldfire SDK's.

5.1. Eclipse

EMAC provides sample code and drivers for the SoM-5282M as CDT projects within the free Eclipse IDE. Eclipse is a powerful open-source Java based IDE. It has plug-ins for Java and C, development and debugging, as well as several other languages.

<http://www.eclipse.org/>

EMAC offers a free download of Eclipse 3.0, complete with JDK 1.4.2, the Eclipse CDT plug-in, and the pre-integrated Tini distribution. We also offer the CTD projects standalone, for easy integration with Eclipse for Linux and Mac users.

<ftp://SoM:sompublic@ftp.emacinc.com/index.html>

5.1.1. Eclipse CDT plug-in

The Eclipse CDT plug-in provides a powerful graphical IDE for C development. This plug-in relies on GNU Make to build its files, so its projects are highly portable to other IDE's (or lack of them completely). It also offers a MI based debugger, for plugging into the newer gdb's.

<http://www.eclipse.org/cdt/>

5.2. Das U-Boot

The SoM-5282M is distributed with Das U-Boot installed. U-Boot is an open source/cross-architecture platform independent bootloader. It supports reading and writing to the flash, auto-booting, environmental variables, and tftp. Das U-boot can be used to upload and run and/or reflash the OS on the SoM-5282M without the use of a BDM cable, or to run stand-alone programs without an OS. SoM-5282M modules are shipped with a valid MAC address installed in flash in the protected ethaddr environmental variable of U-Boot. At boot time U-Boot automatically stores this address in the register of the FEC, which effectively provides it to any OS loaded after that point.

The official Das U-Boot project does not currently fully support the 5282 processor, but a full and open source patched version is available through EMAC. This version contains work by EMAC, and several open source developers and will be released into the main distribution as soon as it is approved.

<http://sourceforge.net/projects/u-boot>

5.3. μ Clinux

μ Clinux is an open source Linux distribution for use with MMU-less systems such as the Coldfire processor. It's a full distribution; build around either a patched 2.4 kernel, or the new 2.6 kernel, which fully supports the embedded m68k architecture. EMAC will support newer kernel version in the future once they become stable.

The distribution contains everything a user could expect from a standard Linux kernel, powerful networking features, advanced file system support, security, gdbserver for source debugging over ethernet, etc...

The SoM-5282M will work out of the box with the standard μ Clinux distribution, and EMAC provides the most up to date distribution via ftp. The SoM-5282M comes preinstalled with a 2.6 build as of the date of this manual.

www.uclinux.org

5.3.1. μ Clinux with RTAI

EMAC also maintains the open source port RTAI to the μ Clinux 2.4 5282 kernel. RTAI provides real time extensions to the kernel and can be used to schedule tasks with hard deadlines and μ s latencies. In the future EMAC will be supporting RTAI on the 2.6 kernel.

www.rtai.org

5.3.2. μ Clinux 2.6 drivers

In addition to standard μ Clinux support, EMAC has released the a number of patches and device drivers from the open source community and from internal EMAC engineering into it's standard distribution. Pending approval from the main tree, these changes will eventually be moved into the main distribution, but are pre-released as stable builds supporting EMAC hardware. All open source 5282 software is stored in the EMAC public CVS, accessible at

Server:	mail.emacinc.com
Repository:	opt.public
Login:	coldfirertai
Passwd:	5282-rtai

Alternatively, the drivers may be downloaded from EMAC's SoM ftp site at <ftp://SoM:sompublic@ftp.emacinc.com>

EMAC μ Clinux drivers are maintained within the EMAC μ Clinux distribution, and as stand-alone Eclipse CDT builds. At the time of this documents writing, the following new drivers/patches were available:

- **EMAC build integration**

The EMAC SoM-5282M vendor option, and new drivers have been added to the μ Clinux build tree, and show up in the high-level configuration menus. Default configuration, device creation, and scripts have been added to vendors/EMAC/SOM5282M/

- **Serial port swap**

EMAC provides a patch to swap serial ports ttyS0 and ttyS2 in software. This reflects the hardware of the SoM-5282, which brings Com1 out it's Com3 port and vice-versa. This is done to enable the use of hardware handshake lines on the third Com port.

- **Enabled Cache**

The current 2.6 kernel disables the Cache of the 5282 by default. This is because originally the Cache of the 5282 was broken. Freescale has since fixed this, however, and all SoM-5282M's ship with fully functional caches. This patch enables the cache in software, greatly increasing the throughput of the processor.

- **QSPI**

The MCF5282 queued SPI driver has been ported and moved into the 2.6 kernel. Also, it's low level calls have be broken out to allow module stacking, which is currently used by the real time clock driver, and will be used by the new SoM-100ES drivers that are currently in development. For details on it's API users are referred to the README within it's project. A test application, loopback.c, is provided in the project which can be used to test the driver and demonstrates how to use it's character driver interface.

- **DS1305 RTC**

The SoM-5282M provides a Dallas Real Time Clock, the DS1305. The DS1305RTC driver stacks on top of the QSPI driver and provides standard real time clock ioctl's for setting and reading the date of the DS1305. Real time clock nodes (/dev/rtc, major 10, minor 135) will hook this driver, so it can be used by the hwclock and date programs(included in the standard distribution) .

- **FEC patch**

A small patch was made to the FEC (fast Ethernet controller)driver to prevent it from disabling the second serial port on initialization. This has already been moved into the main CVS but is not yet available in the standard μ Clinux stable distribution.

5.4. M68k-Elf-Tools

The popular open source gcc compiler has a stable build for the m68k family. Which can be used for building Coldfire applications using the `-m5307` flag. The Das U-boot project, μ Clinux, EMAC Eclipse CDT projects and Codewarrior IDE's all use this compiler for building Coldfire stand alone, and OS specific binaries. Open source patched versions of gdb are available for source level debugging over either the BDM port or over the Ethernet using gdbserver.

<http://gcc.gnu.org/>

Pre-built binaries by the μ Clinux community are available here:

<http://www.uclinux.org/pub/uClinux/m68k-elf-tools/>

5.5. Commercial Solutions

In addition to the open source community, a wide variety of commercial software development solutions are available as well. The most popular probably being Metrowerks CodeWarrior for the Coldfire processor family.

<http://www.metrowerks.com/MW/Develop/Embedded/ColdFire/Default.htm>

Other solutions include the 5282LITE SDK with embedded stack from Viola Systems, Quadros RTX, Micro Digital SMX, as well as a host of others.

5.6. Java

EMAC plans to support Java on the SoM-5282 in the future probably through the use of Waba or SuperWaba. This will allow users of the TINI based SoM-400EM an upgrade path to faster processor.